3,200 ANSI Lumens • WXGA • 3LCD

LC-WNS3200

"Entry" Series Projector

3LCD

Key Features:

- 3,200 ANSI lumens bright with 80% uniformity and a 2400:1 contrast ratio.
- Native WXGA resolution. Compatible with inputs up-to UXGA and WUXGA.
- Supports analog and digital video input in all color standards up-to 1080p.
- HDMI Digital connectivity with HDCP compliance.
- Convenient mid-range (1.2:1) manual zoom and focus lens.
- Fixed image offset. Automatic vertical digital keystone correction.
- Accepts composite, component, and S-Video in all major standards.
- Displays both 4:3 and 16:9 aspect ratios. Supports most HDTV resolutions.
- Built-in 7 Watt sound system. Closed Caption decoding (NTSC).
- Wired network monitoring and control. Digital zoom: 1/4 ~ x16.
- Side-accessed air filter & top accessed lamp for ease of maintenance.
- Color board modes. Custom warm-up screen.
- Auto input selection. Built-in Test Patterns.
- Security bar. Kensington® MicroSaver® security slot. PIN lock.
- 3 year projector warranty.



EIKI 60 YEARS of PROJECTOR EXCELLENCE

EIKI®
Projectors... and more!

LC-WNS3200 SPECIFICATIONS:

Brightness	3,200 ANSI Lumens
Contrast Ratio	2,400:1
Illumination Uniformity	80%
Resolution and Aspect Ratio	WXGA (1280 x 800), 16:10
Color Reproduction	24-bit (16.7 million colors)
Projection Lamp	230 Watts UHP
Estimated Lamp Life	up-to 5,000 Hours
Total Pixels	3,072,000 (1280 x 800) x 3
Imaging System	0.59" (15 mm) LCD Panels x 3
Scanning Frequency	Auto: H Sync. 15 ~ 100 kHz, V Sync. 48 ~ 85 Hz
Pixel Clock	up-to 150 MHz
Lens	Attached ~ Manual Zoom and Focus
Lens Specs	Speed: f : 1.58 ~ 1.75; FL: 0.740 ~ 0.889 in (18.8 ~ 22.6 mm)
Lens Ratios	Zoom Max:Min: 1.2:1; Throw:Width 1.45 ~ 1.74:1
Image Diagonal	40 ~ 300 in (101.6 ~ 762 cm)
Image Width	2.6 ~ 20 ft (0.79 ~ 6.1 m)
Throw Distance	2.9 ~ 35.5 ft (0.88 ~ 10.83 m)
Projector Elevation Adjustment (legs)	up-to 10°
Maximum Pitch	up-to 30° Up or Down
Anti Keystone	Fixed Image Offset, Ratio (Top / Bottom) 13:1
Vertical Keystone Correction	Digital: up-to 30° Up or Down
Image Orientation	Normal, Reversed, Inverted
Local Control / Power Management	Full Function / Auto Shutdown
Remote Control	Wireless x 1
RS-232 Control	Dsub9 x 1
LAN Port	RJ45 x 1
Computer Input in Pixels	up-to 1600 x 1200 (4:3), 1920 x 1200 (16:10)
Analog 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC
Analog Wide Inputs	WUXGA, WSXGA+, WXGA+, WXGA
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC
Digital Wide Inputs	WUXGA, WSXGA+, WXGA+, WXGA
Video Formats	NTSC / PAL / SECAM
Video Input Analog	480i/p, 575i/p
Video Input Digital	480p, 575p, 720p, 1080i/p
Image Signal Resizing	Smart Scaling Technology
Image Signal Inputs	
Computer 1	Dsub15 x 1
Computer 2 (switchable Monitor Out)	Dsub15 x 1
Digital Video (w / HDCP)	HDMI x 1
S-Video	S-Video x 1
Component Video	RCA x 3
Composite Video	RCA x 1
Audio Signal Inputs	
Computer Audio	MiniStereo x 1
Video Audio	RCA x 2 (L/R)
Outputs	
Computer Monitor (Computer 2)	Dsub15 x 1
Audio Output	Variable, Stereo: MiniStereo x 1
Amplifier	Mono: 7 Watt
Speaker	1.4 in (3.7 cm) x 1 (Mono)
Fan Noise	as low as 32 dBA
Cabinet Size (HxWxD)	3.43 x 13.39 x 9.53 in (8.7 x 34.0 x 24.2 cm) (excluding legs)
Weight	6.7 lb (3.05 kg)
Packaged Cabinet Size (HxWxD)	6.7 x 17.0 x 14.2 in (17.0 x 43.1 x 36.0 cm)
Packaged Weight	9.48 lb (4.3 kg)
Operating Temperature	41 ~ 95°F (5 ~ 35°C)
Electrical Safety Compliance	IEC / UL / cUL
Electromagnetic Compatibility	FCC Class B, CE Mark
Power Requirements	100 ~ 240V AC, 50/60 Hz
Power Consumption	0.5 W in Eco Standby mode, up-to 280 W
Heat	up-to 955 BTU/hr
Security Facilities	Kensington® Security Slot
UPC	4571194676488
User Maintenance	Clean Filter, Replace Lamp
Limited Warranty: to the original end-use customer only	
Projector	3 years / 6000 hours (which ever occurs first)
Lamp	1 year ownership / 500 hours use (which ever occurs first)

EIKI® is a registered trademark of EIKI International, Inc. Kensington® is a registered trademark of ACCO Brands Corporation.

Includes a full complement of connections, including network control.

Hg *Lamp Contains Mercury. Do not put in trash. Dispose-of-as Hazardous Waste, according to the laws in your jurisdiction.*

LC-WNS3200 • WXGA projector.

Just project and connect.

Easy to change long-life lamp.

Handy access to air filter.

INCLUDED ACCESSORIES:
Quick Start Guide, Owner's Manual on CD-ROM, VGA Computer Input Cable (Dsub15 to Dsub15), 6.0 ft (1.8 m) Detachable Power Cord, Remote Control (with 2 AAA Batteries).

OPTIONAL ACCESSORIES:
Replacement Lamp, Ceiling Mount, Ceiling Post and Plate, Soft Carry Bag.

Specifications subject to change without notice. ©2013 EIKI International, Inc. Printed in the USA. 10/01/13

EIKI®
Projectors... and more!
www.eiki.com

EIKI International, Inc.
30251 Esperanza △ Rancho Santa Margarita, CA 92688-2130
Phone: 800-242-3454 △ Fax: 800-457-3454 △ E-mail: usa@eiki.com

In Canada: 310 First St.- Unit 2, P.O. Box 156 △ Midland, ON L4R 4K8
Phone: 800-563-3454 △ Fax: 800-567-4069 △ E-mail: canada@eiki.com